

# WL108 SHIPPING DATA



## NOTICE

The information in this publication is for estimating purposes only. Truckload quantities herein were developed for a maximum load weight of 47,000 lbs (21,315 kg) and maximum level load dimensions of 102-in (2.59 m) high x 102-in (2.59 m) wide that provide a 13 ½ ft (4.11 m) overall height when loaded on a flatbed trailer having a 60-in (1.52 m) deck height. See table footnotes for additional information. Special load configurations may be available, and actual truckload quantities may differ from the information in this publication depending upon state, provincial, or federal regulatory requirements, and the size and capacity of commercial equipment available at the time of shipment. WL Plastics Corporation has made every reasonable effort to ensure accuracy, but the information in this publication may not be complete, especially for special or unusual applications. The user of the information in this publication assumes all risk associated with its use. Contact WL Plastics Customer Service for freight information.

**Table 1 Standard Truckload Quantities – Coiled Pipe<sup>1</sup>**

Pipe Size	Coil Length	Pipe DR	Number of Coils per Pallet or Set <sup>2</sup>	Number of Coils per Truckload	Footage per Truckload
1" IPS	500'	7 – 11	7 per pallet	140	70,000
1 1/4" IPS	500'	7 – 11	5 per pallet	100	50,000
1 1/2" IPS	500'	7 – 11	8 per set	64	32,000
	500'	7 – 11	8 per pallet	56	28,000
	2000'	7 – 11	3 per set	24	48,000
2" IPS	500'	7 – 17	7 per set	56	28,000
	500'	7 – 17	7 per pallet	49	24,500
	2000'	7 – 17	2 per set	16	32,000
3" IPS	500'	7 – 17	2 or 4 per set	26	13,000
	1000'	7 – 17	1 or 2 per set	13	13,000
4" IPS	500' <sup>4</sup>	7 – 17	1 or 3 per set	13	6,500
	800'	7 – 17	2 per set	12	9,600

<sup>1</sup> WL Plastics standard coil size and packaging. Special coil sizing or packaging may be available. Contact WL Plastics Customer Service for information. Standard truckload capacity based for 48' long flatbed trailer and DOT maximum load weight and maximum load dimensions 102" high x 102" wide. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> Coils on pallets are laid flat (vertical coil centerline) on non-return wood pallets and strapped in layers to the pallet. Coils packaged in sets are oriented vertically (horizontal coil centerline) and strapped together in sets without pallets or additional dunnage.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



ISO 9001:2008 Certified



CASPER PLANT: 2075 North Pyrite Road • P. O. Box 1120 • Mills, WY 82644 • Customer Service 307-472-6000 • Fax: 307-472-6200  
 CEDAR CITY PLANT: 4660 W. Highway 56 • P. O. Box 627 • Cedar City, UT 84721 • Customer Service 435-867-8908 • Fax: 435-865-2703  
 ELIZABETHTOWN PLANT: 2151 West Park Road • Elizabethtown, KY 42702 • Customer Service 270-765-1020 • Fax: 270-765-1030  
 BOWIE PLANT: 1110 Old Wise Road • PO Box 32 • Bowie, TX 76230 • Customer Service 940-872-8300 • Fax: 940-872-8304  
 CALGARY PLANT: PO Box 860 • 1030 Western Drive • Crossfield, AB T0M 0S0 Canada • Customer Service 403-946-0202 • Fax: 403-946-0252

# WL 108 SHIPPING DATA

**Table 2 Standard Coil Dimensions<sup>1</sup> – Coiled Pipe**

Pipe Size	Coil Length	Pipe DR	Coil Outside Diameter <sup>2</sup> , in.	Coil Inside Diameter <sup>3</sup> , in.	Coil Width <sup>4</sup> , in.
1" IPS	500'	7 – 11	47	30	11 ½
1 1/4" IPS	500'	7 – 11	48	30	15 ½
1 1/2" IPS	500'	7 – 11	74	50	10
	2000'	7 – 11	76 ½	50	31 ½
2" IPS	500'	7 – 17	79	50	13 <sup>5</sup>
	2000'	7 – 17	79	50	44 ½ <sup>6</sup>
3" IPS	500'	7 – 17	96	70	23 <sup>6</sup>
	1000'	7 – 17	96	70	45 <sup>6</sup>
4" IPS	500'	7 – 17	96	70	40 <sup>6, 7</sup>
	800'	7 – 17	102	70	46 <sup>6</sup>

<sup>1</sup> WL Plastics standard coil packaging. Special packaging and coil lengths may be available. Contact WL Plastics Customer Service for information.

<sup>2</sup> Outside diameter dimensions are approximate. The tail end of the coil is strapped to the coil body to the extent practical, but may extend beyond the coil outside diameter by up to 3 pipe diameters.

<sup>3</sup> Inside diameter dimensions are approximate, and may include a small taper from one side of the coil to the other.

<sup>4</sup> Coil width dimensions are approximate.

<sup>5</sup> 12 ¾" wide for DR17.

<sup>6</sup> 1" wider for DR17.

<sup>7</sup> Contact WL Plastics Customer Service for special coil sizing.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



ISO 9001:2008 Certified



CASPER PLANT: 2075 North Pyrite Road • P. O. Box 1120 • Mills, WY 82644 • Customer Service 307-472-6000 • Fax: 307-472-6200  
 CEDAR CITY PLANT: 4660 W. Highway 56 • P. O. Box 627 • Cedar City, UT 84721 • Customer Service 435-867-8908 • Fax: 435-865-2703  
 ELIZABETHTOWN PLANT: 2151 West Park Road • Elizabethtown, KY 42702 • Customer Service 270-765-1020 • Fax: 270-765-1030  
 BOWIE PLANT: 1110 Old Wise Road • PO Box 32 • Bowie, TX 76230 • Customer Service 940-872-8300 • Fax: 940-872-8304  
 CALGARY PLANT: PO Box 860 • 1030 Western Drive • Crossfield, AB T0M 0S0 Canada • Customer Service 403-946-0202 • Fax: 403-946-0252

## Table 3A Standard Truckload Quantities – IPS Pipe Joints<sup>1</sup>

IPS Pipe Size	Joint Length, ft x Joints / Bundle	Pipe DR	No. of Bundles per Truckload	Footage per Truckload	Joint Length, ft x Joints / Bundle	Pipe DR	No. of Bundles per Truckload	Footage per Truckload	
2	40 x 99	5 – 6	10	39,600	40 x 50	5	18	36,000	
		6.3 – 7.3	12	47,520		6 – 6.3	20	44,000	
		9 – 17	14	55,440		7 – 17	24	48,000	
2 ½	40 x 44	5	14	24,640					
		6	16	28,160					
		6.3 – 7	18	31,680					
		7.3 – 17	20	35,200					
3	40 x 50	5	8	16,000					
		6 – 6.3	10	20,000					
		7 – 7.3	12	24,000					
		9 – 21	14	28,000					
4	40 x 57	7 – 7.3 <sup>2</sup>	6	13,680	50 x 57	9 – 11 <sup>2</sup>	6	17,100	
		9 – 32.5	8	18,240		13.5 – 32.5	8	22,800	
	40 x 29	5	8	9,280	50 x 29	5	6	8,700	
		6 – 6.3	10	11,600		6 – 6.3	8	11,600	
		7 – 7.3	12	13,920		7 – 7.3	10	14,500	
		9	14	16,240		9	12	17,400	
		11 – 32.5	16	18,580		11	14	20,300	
						13.5 – 32.5	16	23,200	
	40 x 19	5	14	10,640	50 x 19	5	10	9,500	
		6 – 6.3	16	12,180		6 – 6.3	12	11,400	
		7 – 7.3	18	13,680		7 – 7.3	14	13,300	
		9 – 32.5	22	16,720		9	18	17,100	
5	40 x 38	7 – 9 <sup>2</sup>	6	9,120	50 x 38	9 – 11 <sup>2</sup>	6	11,400	
		11 – 32.5	8	12,160		13.5 – 32.5	8	15,200	
	40 x 23	5 – 6.3	8	7,360	50 x 23	5 – 6.3	6	6,900	
		7 – 7.3	10	9,200		7 – 7.3	8	9,200	
		9 – 32.5	12	11,040		9	10	11,500	
						11 – 32.5	12	13,800	

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high). Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information. <sup>2</sup> Bundle configuration not available for lower DR's because bundle weight exceeds 8,000 lbs (3640 kg).

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



ISO 9001:2008 Certified



CASPER PLANT: 2075 North Pyrite Road • P. O. Box 1120 • Mills, WY 82644 • Customer Service 307-472-6000 • Fax: 307-472-6200  
 CEDAR CITY PLANT: 4660 W. Highway 56 • P. O. Box 627 • Cedar City, UT 84721 • Customer Service 435-867-8908 • Fax: 435-865-2703  
 ELIZABETHTOWN PLANT: 2151 West Park Road • Elizabethtown, KY 42702 • Customer Service 270-765-1020 • Fax: 270-765-1030  
 BOWIE PLANT: 1110 Old Wise Road • PO Box 32 • Bowie, TX 76230 • Customer Service 940-872-8300 • Fax: 940-872-8304  
 CALGARY PLANT: PO Box 860 • 1030 Western Drive • Crossfield, AB T0M 0S0 Canada • Customer Service 403-946-0202 • Fax: 403-946-0252

# WL 108 SHIPPING DATA



**Table 3B Standard Truckload Quantities – IPS Pipe Joints<sup>1</sup>**

IPS Pipe Size	Joint Length, ft x Joints / Bundle	Pipe DR	No. of Bundles per Truckload	Footage per Truckload	Joint Length, ft x Joints / Bundle	Pipe DR	No. of Bundles per Truckload	Footage per Truckload
6	40 x 20	5 – 6.3	6	4,800	50 x 20	6.3 – 7.3 <sup>2</sup>	6	6,000
		7 – 7.3	8	4,800		9	8	8,000
		9 – 32.5	10	8,000		11 – 32.5	10	10,000
	40 x 13	5	8	4,160	50 x 13	5 – 6.3	8	5,200
		6 – 6.3	10	5,200		7 – 7.3	10	6,500
		7 – 7.3	12	6,240		9	12	7,800
		9	14	7,280		11	14	9,100
		11 – 32.5	16	8,320		13.5 – 32.5	16	10,400
8	40 x 14	6 – 7.3 <sup>2</sup>	6	3,360	50 x 14	9 <sup>2</sup>	6	4,200
		9 – 32.5	8	4,480		11 – 32.5	8	5,600
	40 x 9	5 – 6	8	2,880	50 x 9	5 – 6	6	2,700
		6.3 – 7.3	10	3,600		6.3 – 7.3	8	3,600
		9 – 32.5	12	4,320		9	10	4,500
	40 x 5				50 x 5	11 – 32.5	12	5,400
		5	14	2,800		5 – 6	12	3,000
		6 – 6.3	16	3,200		6.3 – 7	14	3,500
		7	18	3,600		7.3	16	4,000
		7.3	20	4,000		9	18	4,500
		9 – 32.5	22	4,400	11 – 32.5	22	5,500	

IPS Pipe Size	Pipe Joint Length, ft	Pipe DR	No of Joints per Truckload	Footage per Truckload	Pipe Joint Length, ft	Pipe DR	No of Joints per Truckload	Footage per Truckload
10	40	5	45	1,800	50	5 – 6	36	1,800
		6 – 7	54	2,160		6.3 – 7.3	45	2,250
		7.3	63	2,520		9	54	2,700
		9 – 32.5	72	2,880		11 – 32.5	72	3,600
12	40	5 – 6	32	1,280	50	5 – 6	24	1,200
		6.3 – 7.3	40	1,600		6.3 – 7.3	32	1,600
		9	48	1,920		9	40	2,000
		11 – 32.5	56	2,240		11	48	2,400
					13.5 – 32.5	56	2,800	

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high). Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information. <sup>2</sup> Bundle configuration not available for lower DR's because bundle weight exceeds 8,000 lbs (3640 kg).

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.

# WL108 SHIPPING DATA



**Table 3C Standard Truckload Quantities – IPS Pipe Joints<sup>1</sup>**

IPS Pipe Size	Pipe Joint Length, ft	Pipe DR	No of Joints per Truckload	Footage per Truckload	Pipe Joint Length, ft	Pipe DR	No of Joints per Truckload	Footage per Truckload
14	40	5 – 6.3	28	1,120	50	5 – 6.3	21	1,050
		7 – 7.3	35	1,400		7 – 7.3	28	1,400
		9 – 32.5	42	1,680		9	35	1,750
16	40	5	18	720	50	5	12	600
		6 – 7.3	24	960		6 – 7.3	18	900
		9 – 32.5	30	1,200		9	24	1,200
						11 – 32.5	30	1,500
18	40	5 – 6	15	600	50	5	10	500
		6.3 – 7.3	20	800		6 – 7.3	15	750
		9 – 32.5	25 <sup>2</sup>	1000		9	20	1,000
						11 – 32.5	25 <sup>2</sup>	1,250
20	40	6 – 7.3	15	600	50	6 – 7	10	500
		9 – 32.5	20	800		7.3 – 9	15	750
						11 – 32.5	20	1,000
22	40	6 – 7.3	12	480	50	6 – 6.3	8	400
		9 – 32.5	16	640		7 – 9	12	600
						11 – 32.5	16	800
24	40	6.3	8	320	50	6.3 – 7.3	8	400
		7 – 9	12	480		9 – 11	12	600
		11 – 32.5	16 <sup>2</sup>	640		13.5 – 32.5	16 <sup>2</sup>	800
26	40	7 – 32.5	9	360	50	7 – 7.3	6	300
						9 – 32.5	9	450
28	40	7.3 – 32.5	9	360	50	7.3	6	300
						9 – 32.51	9	450
30	40	9 – 32.5	9	360	50	9	6	300
						11 – 32.5	9	450
32	40	9 – 32.5	6	240	50	9 – 32.5	6	300
34	40	9 – 32.5	6	240	50	9 – 32.5	6	300
36	40	11 – 32.5	4	160	50	11 – 32.5	4	200
42	40	11 – 32.5	4	160	50	11 – 32.5	4	200
48	40	13.5 – 32.5	4	160	50	13.5 – 32.5	4	200
54	40	15.5 – 32.5	2	80	50	15.5 – 32.5	2	100

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high). Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information. <sup>2</sup> Load may be subject to height restrictions.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



ISO 9001:2008 Certified



CASPER PLANT: 2075 North Pyrite Road • P. O. Box 1120 • Mills, WY 82644 • Customer Service 307-472-6000 • Fax: 307-472-6200  
 CEDAR CITY PLANT: 4660 W. Highway 56 • P. O. Box 627 • Cedar City, UT 84721 • Customer Service 435-867-8908 • Fax: 435-865-2703  
 ELIZABETHTOWN PLANT: 2151 West Park Road • Elizabethtown, KY 42702 • Customer Service 270-765-1020 • Fax: 270-765-1030  
 BOWIE PLANT: 1110 Old Wise Road • PO Box 32 • Bowie, TX 76230 • Customer Service 940-872-8300 • Fax: 940-872-8304  
 CALGARY PLANT: PO Box 860 • 1030 Western Drive • Crossfield, AB T0M 0S0 Canada • Customer Service 403-946-0202 • Fax: 403-946-0252

# WL108 SHIPPING DATA



**Table 4A Standard Truckload Quantities – DIPS (DIOD) Pipe Joints <sup>1</sup>**

DIPS Pipe Size	Joint Length, ft x Joints / Bundle	Pipe DR	No. of Bundles per Truckload	Footage per Truckload	Joint Length, ft x Joints / Bundle	Pipe DR	No. of Bundles per Truckload	Footage per Truckload
4	40 x 57	9 <sup>2</sup> – 32.5	6	13,680	50 x 57	11 <sup>2</sup> – 32.5	6	17,100
		5 – 6.3	6	9,120		6.3 – 7.3 <sup>2</sup>	6	11,400
	40 x 38	7 – 7.3	8	12,160	50 x 38	9	8	15,200
		9 – 13.5	10	15,200		11 – 32.5	10	19,000
6	40 x 26	7.3 – 9 <sup>2</sup>	6	6,240	50 x 26	9 – 11 <sup>2</sup>	6	7,800
		11 – 32.5	8	8,320		13.5 – 32.5	8	10,400
	40 x 13	5	10	4,400	50 x 13	5	8	4,400
		6 – 7	12	5,280		6 – 7.3	10	5,500
		7.3 – 32.5	14	6,160		9	12	6,600
						11 – 32.5	14	7,700
8	40 x 14	7 – 7.3 <sup>2</sup>	6	3,360	50 x 14	9 – 11 <sup>2</sup>	6	4,200
		9 – 32.5	8	4,480		13.5 – 32.5	8	5,600
	40 x 9	5	6	2,160	50 x 9	6 – 6.3 <sup>2</sup>	6	2,700
		6 – 6.3	8	2,280		7 – 9	8	3,600
	40 x 5	7 – 32.5	10	3,600	50 x 5	11 – 32.5	10	4,500
		5	12	2,400		5	10	2,500
		6	14	2,800		6 – 6.3	12	3,000
		6.3 – 7	16	3,200		7 – 7.3	14	3,500
		7.3	18	3,600		9	16	4,000
		9	20	4,000		11	20	5,000
	11 – 32.5	22	4,400	13.5 – 32.5	22	5,500		

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high). Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information. <sup>2</sup> Bundle configuration not available for lower DR's because bundle weight exceeds 8,000 lbs (3640 kg).

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



ISO 9001:2008 Certified



CASPER PLANT: 2075 North Pyrite Road • P. O. Box 1120 • Mills, WY 82644 • Customer Service 307-472-6000 • Fax: 307-472-6200  
 CEDAR CITY PLANT: 4660 W. Highway 56 • P. O. Box 627 • Cedar City, UT 84721 • Customer Service 435-867-8908 • Fax: 435-865-2703  
 ELIZABETHTOWN PLANT: 2151 West Park Road • Elizabethtown, KY 42702 • Customer Service 270-765-1020 • Fax: 270-765-1030  
 BOWIE PLANT: 1110 Old Wise Road • PO Box 32 • Bowie, TX 76230 • Customer Service 940-872-8300 • Fax: 940-872-8304  
 CALGARY PLANT: PO Box 860 • 1030 Western Drive • Crossfield, AB T0M 0S0 Canada • Customer Service 403-946-0202 • Fax: 403-946-0252

# WL108 SHIPPING DATA



**Table 4B Standard Truckload Quantities – DIPS (DIOD) Pipe Joints 1**

DIPS Pipe Size	Pipe Joint Length, ft	Pipe DR	No of Joints per Truckload	Footage per Truckload	Pipe Joint Length, ft	Pipe DR	No of Joints per Truckload	Footage per Truckload
10	40	5	36	1,440	50	5	27	1,350
		6 – 6.3	45	1,800		6 – 6.3	36	1,800
		7 – 7.3	54	2,160		7 – 7.3	45	2,250
		9	63	2,520		9	54	2,700
		11 – 32.5	72	2,880		11	63	3,150
					13.5 – 32.5	72	3,600	
12	40	5	28	1,120	50	5	21	1,050
		6 – 7	35	1,400		6 – 7.3	28	1,400
		7.3 – 32.5	42	1,680		9	35	1,750
					11 – 32.5	42	2,100	
14	40	5	18	720	50	5 – 6.3	18	900
		6.3 – 6.3	24	960		7 – 7.3	24	1,200
		7 – 7.3	30	1,200		9	30	1,500
		9 – 32.5	36	1,440		11 – 32.5	36	1,800
16	40	5	15	600	50	5	10	500
		6 – 32.5	20	800		6 – 7.3	15	750
						9 – 32.5	20	1,000
18	40	6 – 7.3	15	600	50	6 – 6.3	10	500
		9 – 32.5	20	800		7 – 9	15	750
						11 – 32.5	20	1,000
20	40	6 – 7	12	480	50	6 – 6.3	8	400
		7.3 – 32.5	16	640		7 – 9	12	600
					11 – 32.5	16	800	
24	40	7 – 32.5	9	360	50	7	6	300
						7.3 – 32.5	9	450
30	40	9 – 32.5	6	240	50	9 – 32.5	6	300

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high). Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



ISO 9001:2008 Certified



CASPER PLANT: 2075 North Pyrite Road • P. O. Box 1120 • Mills, WY 82644 • Customer Service 307-472-6000 • Fax: 307-472-6200  
 CEDAR CITY PLANT: 4660 W. Highway 56 • P. O. Box 627 • Cedar City, UT 84721 • Customer Service 435-867-8908 • Fax: 435-865-2703  
 ELIZABETHTOWN PLANT: 2151 West Park Road • Elizabethtown, KY 42702 • Customer Service 270-765-1020 • Fax: 270-765-1030  
 BOWIE PLANT: 1110 Old Wise Road • PO Box 32 • Bowie, TX 76230 • Customer Service 940-872-8300 • Fax: 940-872-8304  
 CALGARY PLANT: PO Box 860 • 1030 Western Drive • Crossfield, AB T0M 0S0 Canada • Customer Service 403-946-0202 • Fax: 403-946-0252

# SHIPPING DATA

**Table 5 Standard Truckload Quantities – FM Pipe Joints<sup>1</sup>**

IPS Pipe Size	Joint Length, ft x Joints / Bundle	Pipe Class	Bundles per Truckload	Footage per Truckload	Joint Length, ft x Joints / Bundle	Pipe Class	Bundles per Truckload	Footage per Truckload
4	40 x 57	150	8	18,240	50 x 57	150	8	22,800
		200	8	18,240		200	6	17,100
	40 x 29	150	16	18,560	50 x 29	150	14	20,300
		200	14	16,240		200	12	17,400
	40 x 19	150	22	16,720	50 x 19	150	22	20,900
		200	22	16,720		200	18	17,100
6	40 x 20	150	10	8,000	50 x 20	150	10	10,000
		200	10	8,000		200	8	8,000
	40 x 13	150	16	8,320	50 x 13	150	14	9,100
		200	14	7,280		200	12	7,800
8	40 x 14	150	8	4,480	50 x 14	150	8	5,600
		200	8	4,480		200	6	4,200
	40 x 9	150	12	4,320	50 x 9	150	12	5,400
		200	12	4,320		200	10	4,500
	40 x 5	150	22	4,400	50 x 5	150	22	5,500
		200	22	4,400		200	18	4,500

  

IPS Pipe Size	Pipe Joint Length, ft	Pipe Class	Joints per Truckload	Footage per Truckload	Pipe Joint Length, ft	Pipe Class	Joints per Truckload	Footage per Truckload
10	40	150	72	2,880	50	150	72	3,600
		200	72	2,880		200	54	2,700
12	40	150	56	2,240	50	150	48	2,400
		200	48	1,920		200	40	2,000
14	40	150	42	1,680	50	150	42	2,100
		200	42	1,680		200	35	1,750
16	40	150	30	1,200	50	150	30	1,500
		200	30	1,200		200	24	1,200
18	40	150	20	800	50	150	20	1,000
		200	20	800		200	20	1,000
20	40	150	20	800	50	150	20	1,000
		200	20	800		200	15	750
22	40	150	16	640	50	150	16	800
		200	16	640		200	12	600
24	40	150	16 <sup>2</sup>	640	50	150	12	600
		200	12	480		200	12	600

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high). Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information. <sup>2</sup> Load may be subject to height restrictions.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



ISO 9001:2008 Certified



CASPER PLANT: 2075 North Pyrite Road • P. O. Box 1120 • Mills, WY 82644 • Customer Service 307-472-6000 • Fax: 307-472-6200  
 CEDAR CITY PLANT: 4660 W. Highway 56 • P. O. Box 627 • Cedar City, UT 84721 • Customer Service 435-867-8908 • Fax: 435-865-2703  
 ELIZABETHTOWN PLANT: 2151 West Park Road • Elizabethtown, KY 42702 • Customer Service 270-765-1020 • Fax: 270-765-1030  
 BOWIE PLANT: 1110 Old Wise Road • PO Box 32 • Bowie, TX 76230 • Customer Service 940-872-8300 • Fax: 940-872-8304  
 CALGARY PLANT: PO Box 860 • 1030 Western Drive • Crossfield, AB T0M 0S0 Canada • Customer Service 403-946-0202 • Fax: 403-946-0252